

LMS3000TRA & LMS3000MM



TWO POST LIFTS

Features include:

- Triple reach front arms as standard approved by BMW
- 3000 Kg lifting capacity
- Low wear Nylatron-nut set
- Quiet operation
- Twin motors integrated into columns
- Power transmission by multiple V-belt
- Clear floor, no base frame
- Complete control at all stages
- Electronic synchronisation
- Low lifting point from 95mm (75mm with MM arms)
- Short lifting asymmetric arms, swivelling 180° for easy access
- Cable duct height adjustable. 3716-4167 mm
- 3 phase motor
- 2 year comprehensive warranty on all electrical parts
- Available in blue (RAL 5002) or grey (RAL 7016)



MODEL	LMS3000TRA	LMS3000MM
Lifting Capacity (Kg)	3000	3000
Lifting/Lowering Time Approx (secs)	40/40	40/40
Lifting Height (mm)	1983	1983
Lowest Lifting Point (mm)	95-140	75-185
Overall Height (mm)	2887	2887
Min Ceiling Height Required (mm)	3200	3200
Overall Width (mm)	3000/3100	3000/3100
Drive Through Width (mm)	2230/2330	2230/2330
Distance Between Posts (mm)	2460/2560	2460/2560
Long Arm Extraction (mm)	940-1495	1000-1480
Short Arm Extraction (mm)	480-870	600-980
Motor (Kw)	2 X 1.5	2 x 1.5
Power Supply V/Hz)	400/50	400/50

Options:

- Mini Max Lifting Arms (MM)



- * Easy access for vehicles with side skirts
- * Height adjustable lifting pads
- * Enormous adjustable range
- * Multi level adjustment through pedals
- * Reliable Positioning

- Height Adapters



- * Adjustable height adapter (160mm - 240mm)
- * Sold as set of 4
- * To facilitate lifting 4 x 4's and vans

